

## **DELIVERY OF AEROSOLS CONTAINING SMALL PARTICLES THROUGH AN INHALATION ROUTE**

[001] This application is a continuation of U.S. patent application Ser. No. 10/146,515 entitled "Delivery of Aerosols Containing Small Particles Through an Inhalation Route," filed May 13, 2002, which is a continuation-in-part of U.S. patent application Ser. No. 10/057,198 entitled "Method and Device for Delivering a Physiologically Active Compound," filed October 26, 2001, Lloyd et al. and of U.S. patent application Ser. No. 10/057,197 entitled "Aerosol Generating Device and Method," filed October 26, 2001, Wensley et al., both of which are hereby incorporated by reference for all purposes. This application further claims priority to U.S. provisional application Ser. No. 60/296,225 entitled "Aerosol Generating Device and Method," filed June 5, 2001, Wensley et al., the entire disclosure of which is hereby incorporated by reference.

### **FIELD OF THE INVENTION**

[002] The present invention relates to the inhalation delivery of aerosols containing small particles. Specifically, it relates to the delivery of drug containing aerosols having particles with a mass median aerodynamic diameter less than 1  $\mu$  for inhalation therapy.

### **BACKGROUND OF THE INVENTION**

[003] Currently, there are a number of approved devices for the inhalation delivery of drugs, including dry powder inhalers, nebulizers, and pressurized metered dose inhalers. A typical goal of these devices is to produce an aerosol containing drug particles with a mass median aerodynamic diameter between 1  $\mu$  and 10  $\mu$ .

[004] It is desirable to provide aerosols having particles with a mass median aerodynamic diameter less than 1  $\mu$ . The provision of such aerosols is an object of the present invention.

## SUMMARY OF THE INVENTION

**[005]** The present invention relates to the inhalation delivery of aerosols containing small particles. Specifically, it relates to the delivery of drug containing aerosols having particles with a mass median aerodynamic diameter less than 1  $\mu$  for inhalation therapy.

**[006]** In a composition aspect of the present invention the drug containing aerosol contains particles having a mass median aerodynamic diameter between 10 nm and 1 $\mu$ . Preferably the particles have a mass median aerodynamic diameter between 10 nm and 900 nm. More preferably, the particles have a mass median aerodynamic diameter between 10 nm and 800 nm, 10 nm and 700 nm, 10 nm and 600 nm, 10 nm and 500 nm, 10 nm and 400 nm, 10 nm and 300 nm, 10 nm and 200 nm, or 10 nm and 100 nm.

**[007]** Typically, the particles comprise at least 5 percent by weight of drug. Preferably, the particles comprise at least 10 percent by weight of drug. More preferably, the particles comprise at least 20 percent, 30 percent, 40 percent, 50 percent, 60 percent, 70 percent, 80 percent, 90 percent, 95 percent, 97 percent, 99 percent, 99.5 percent, or 99.97 percent by weight of drug.

**[008]** Typically, at least 50 percent by weight of the aerosol is amorphous in form, wherein crystalline forms make up less than 50 percent by weight of the total aerosol weight, regardless of the nature of individual particles. Preferably, at least 75 percent by weight of the aerosol is amorphous in form. More preferably, at least 90 percent by weight of the aerosol is amorphous in form.

**[009]** Typically, the aerosol comprises less than 10 percent by weight of drug degradation products. Preferably, the particles contain less than 5 percent of drug degradation products. More preferably, the particles contain less than 2.5, 1, 0.5, 0.1 or 0.03 percent by weight of drug degradation products.

**[010]** Typically, the mass of the aerosol is at least 0.05 mg. Preferably, the mass of the aerosol is at least 0.10 mg. More preferably, the mass of the aerosol is at least 0.15 mg, 0.20 mg, or 0.25 mg.

**[011]** Typically, the geometric standard deviation around the mass median aerodynamic diameter of the aerosol particles is less than 2. Preferably, the geometric standard deviation is less than 1.9. More preferably, the geometric standard deviation is less than 1.8, 1.7, 1.6 or 1.5.

**[012]** Typically, the drug has a decomposition index less than 0.15. Preferably, the drug has a decomposition index less than 0.10. More preferably, the drug has a decomposition index less than 0.05.

**[013]** Typically, the drug of the aerosol is of one of the following classes: antibiotics, anticonvulsants, antidepressants, antiemetics, antihistamines, antiparkinsonian drugs, antipsychotics, anxiolytics, drugs for erectile dysfunction, drugs for migraine headaches, drugs for the treatment of alcoholism, drugs for the treatment of addiction, muscle relaxants, nonsteroidal anti-inflammatories, opioids, other analgesics and stimulants.

**[014]** Typically, where the drug is an antibiotic, it is selected from one of the following compounds: cefmetazole; cefazolin; cephalixin; cefoxitin; cephacetrile; cephaloglycin; cephaloridine; cephalosporins, such as cephalosporin C; cephalotin; cephamycins, such as cephamycin A, cephamycin B, and cephamycin C; cepharin; cephradine; ampicillin; amoxicillin; hetacillin; carfecillin; carindacillin; carbenicillin; amylpenicillin; azidocillin; benzylpenicillin; clometocillin; cloxacillin; cyclacillin; methicillin; nafcillin; 2-pentenylpenicillin; penicillins, such as penicillin N, penicillin O, penicillin S, penicillin V; chlorobutin penicillin; dicloxacillin; diphenicillin; heptylpenicillin; and metampicillin.

**[015]** Typically, where the drug is an anticonvulsant, it is selected from one of the following compounds: gabapentin, tiagabine, and vigabatrin.

**[016]** Typically, where the drug is an antidepressant, it is selected from one of the following compounds: amitriptyline, amoxapine, benmoxine, butriptyline, clomipramine, desipramine, dosulepin, doxepin, imipramine, kitanserin, lofepramine, medifoxamine, mianserin, maprotiline, mirtazapine, nortriptyline, protriptyline, trimipramine, viloxazine, citalopram, cotinine, duloxetine, fluoxetine, fluvoxamine, milnacipran, nisooxetine, paroxetine, reboxetine, sertraline, tianeptine, acetaphenazine, binedaline, brofaromine, cericlamine, clovoxamine, iproniazid, isocarboxazid, moclobemide, phenylhydrazine, phenelzine, selegiline, sibutramine, tranlycypromine, ademetionine, adrafinil, amesergide, amisulpride, amperozide, benactyzine, bupropion, caroxazone, gepirone, idazoxan, metralindole, milnacipran, minaprine, nefazodone, nomifensine, ritanserin, roxindole, S-adenosylmethionine, tofenacin, trazodone, tryptophan, venlafaxine, and zalospirone.

**[017]** Typically, where the drug is an antiemetic, it is selected from one of the following compounds: alizapride, azasetron, benzquinamide, bromopride, buclizine, chlorpromazine,

cinnarizine, clebopride, cyclizine, diphenhydramine, diphenidol, dolasetron methanesulfonate, droperidol, granisetron, hyoscine, lorazepam, metoclopramide, metopimazine, ondansetron, perphenazine, promethazine, prochlorperazine, scopolamine, triethylperazine, trifluoperazine, triflupromazine, trimethobenzamide, tropisetron, domeridone, and palonosetron.

**[018]** Typically, where the drug is an antihistamine, it is selected from one of the following compounds: azatadine, brompheniramine, chlorpheniramine, clemastine, cyproheptadine, dexmedetomidine, diphenhydramine, doxylamine, hydroxyzine, cetirizine, fexofenadine, loratidine, and promethazine.

**[019]** Typically, where the drug is an antiparkinsonian drug, it is selected one of the following compounds: amantadine, baclofen, biperiden, benztropine, orphenadrine, procyclidine, trihexyphenidyl, levodopa, carbidopa, selegiline, deprenyl, andropinirole, apomorphine, benserazide, bromocriptine, budipine, cabergoline, dihydroergokryptine, eliprodil, eptastigmine, ergoline pramipexole, galanthamine, lazabemide, lisuride, mazindol, memantine, mofegiline, pergolike, pramipexole, propentofylline, rasagiline, remacemide, spheramine, terguride, entacapone, and tolcapone.

**[020]** Typically, where the drug is an antipsychotic, it is selected from one of the following compounds: acetophenazine, alizapride, amperozide, benperidol, benzquinamide, bromperidol, buramate, butaperazine, carphenazine, carpipramine, chlorpromazine, chlorprothixene, clocapramine, clomacran, clopenthixol, clospirazine, clothiapine, cyamemazine, droperidol, flupenthixol, fluphenazine, fluspirilene, haloperidol, mesoridazine, metofenazate, molindrone, penfluridol, pericyazine, perphenazine, pimozide, pipamerone, piperacetazine, pipotiazine, prochlorperazine, promazine, remoxipride, sertindole, spiperone, sulpiride, thioridazine, thiothixene, trifluoperidol, triflupromazine, trifluoperazine, ziprasidone, zotepine, zuclopenthixol, amisulpride, butaclamol, clozapine, melperone, olanzapine, quetiapine, and risperidone.

**[021]** Typically, where the drug is an anxiolytic, it is selected from one of the following compounds: mecloqualone, medetomidine, metomidate, adinazolam, chlordiazepoxide, clobenzepam, flurazepam, lorazepam, loprazolam, midazolam, alpidem, alseroxlon, amphenidone, azacyclonol, bromisovalum, buspirone, calcium N-carboamoylaspartate, captodiamine, capuride, carbcloral, carbromal, chloral betaine, enciprazine, flesinoxan,

ipsapiraone, lesopitron, loxapine, methaqualone, methprylon, propanolol, tandospirone, trazadone, zopiclone, and zolpidem.

**[022]** Typically, where the drug is a drug for erectile dysfunction, it is selected from one of the following compounds: cialis (IC351), sildenafil, vardenafil, apomorphine, apomorphine diacetate, phentolamine, and yohimbine.

**[023]** Typically, where the drug is a drug for migraine headache, it is selected from one of the following compounds: almotriptan, alperopride, codeine, dihydroergotamine, ergotamine, eletriptan, frovatriptan, isometheptene, lidocaine, lisuride, metoclopramide, naratriptan, oxycodone, propoxyphene, rizatriptan, sumatriptan, tolfenamic acid, zolmitriptan, amitriptyline, atenolol, clonidine, cyproheptadine, diltiazem, doxepin, fluoxetine, lisinopril, methysergide, metoprolol, nadolol, nortriptyline, paroxetine, pizotifen, pizotyline, propanolol, protriptyline, sertraline, timolol, and verapamil.

**[024]** Typically, where the drug is a drug for the treatment of alcoholism, it is selected from one of the following compounds: naloxone, naltrexone, and disulfiram.

**[025]** Typically, where the drug is a drug for the treatment of addiction it is buprenorphine.

**[026]** Typically, where the drug is a muscle relaxant, it is selected from one of the following compounds: baclofen, cyclobenzaprine, orphenadrine, quinine, and tizanidine.

**[027]** Typically, where the drug is a nonsteroidal anti-inflammatory, it is selected from one of the following compounds: aceclofenac, alminoprofen, amfenac, aminopropylon, amixetrine, benoxaprofen, bromfenac, bufexamac, carprofen, choline, salicylate, cinchophen, cinmetacin, clopiac, clometacin, diclofenac, etodolac, indoprofen, mazipredone, meclofenamate, piroxicam, piroprofen, and tolfenamate.

**[028]** Typically, where the drug is an opioid, it is selected from one of the following compounds: alfentanil, allylprodine, alphaprodine, anileridine, benzylmorphine, bezitramide, buprenorphine, butorphanol, carbiphen, cipramadol, clonitazene, codeine, dextromoramide, dextropropoxyphene, diamorphine, dihydrocodeine, diphenoxylate, dipipanone, fentanyl, hydromorphone, L-alpha acetyl methadol, lofentanil, levorphanol, meperidine, methadone, meptazinol, metopon, morphine, nalbuphine, nalorphine, oxycodone, papaveretum, pethidine, pentazocine, phenazocine, remifentanil, sufentanil, and tramadol.

[029] Typically, where the drug is an other analgesic it is selected from one of the following compounds: apazone, benzpiperylon, benzydamine, caffeine, clonixin, ethoheptazine, flupirtine, nefopam, orphenadrine, propacetamol, and propoxyphene.

[030] Typically, where the drug is a stimulant, it is selected from one of the following compounds: amphetamine, brucine, caffeine, dexfenfluramine, dextroamphetamine, ephedrine, fenfluramine, mazindol, methyphenidate, pemoline, phentermine, and sibutramine.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

[031] Further features and advantages will become apparent from the following description of various examples of the invention, as illustrated in the accompanying drawings in which:

[032] FIG. 1 is a schematic diagram of the overall system for conducting experiments using a laboratory example of a device of the present invention;

[033] FIG. 2 is a top, right end and front perspective view of the example depicted in FIG. 1;

[034] FIG. 3 is a partial cross-sectional and partial schematic side view of the example shown in FIG. 2;

[035] FIG. 4 is a partial cross-sectional and partial schematic end view of the example shown in FIG. 2;

[036] FIG. 5 is a partial cross-sectional and partial schematic top view of the example shown in FIG. 2;

[037] FIG. 6 is a schematic cross-sectional side view of an alternate example of the device of the present invention using an annunciating device;

[038] FIG. 7 is a top, left end and front perspective views of the removable sub-assembly containing the compound and a movable slide of the example shown in FIG. 2 showing the sub-assembly being mounted within the slide;

[039] FIG. 8 is a schematic view of the heating element of the example shown in FIG. 2 showing the electric drive circuit;

[040] FIG. 9 is a schematic side view of a second example of the present invention using a venturi tube;

- [041] FIG. 10 is a schematic side view of a fourth example of the present invention using a thin-walled tube coated with the compound;
- [042] FIG. 11 is a schematic side end view of the example shown in FIG. 10;
- [043] FIG. 12 is a schematic side end view of the example shown in FIG. 10 showing an inductive heating system generating an alternating magnetic field;
- [044] FIG. 13 is a schematic side view of an alternate example of that shown in FIG. 10 using a flow restrictor within the thin-walled tube;
- [045] FIG. 14 is a schematic side view of a fifth example of the present invention using an expandable container for the compound;
- [046] FIG. 15 is a schematic side view of a sixth example of the present invention using a container for the compound in an inert atmosphere;
- [047] FIG. 16 is a schematic side view of the example shown in FIG. 15 using a re-circulation of the inert atmosphere over the compound's surface;
- [048] FIG. 17 is a schematic side view of a seventh example of the present invention using a tube containing particles coated with the compound;
- [049] FIG. 18 is a schematic side view of the example shown in FIG. 17 using a heating system to heat the gas passing over the coated particles;
- [050] FIG. 19 is a schematic side view of an eighth example of the present invention referred to herein as the "oven device";
- [051] FIG. 20 is a schematic side view of a ninth example of the present invention using gradient heating;
- [052] FIG. 21 is a schematic side view of a tenth example of the present invention using a fine mesh screen coated with the compound;
- [053] FIG. 22 is a top, right end and front perspective view of the example shown in FIG. 21;
- [054] FIG. 23 is a plot of the rate of aggregation of smaller particles into larger ones;
- [055] FIG. 24 is a plot of the coagulation coefficient (K) versus particle size of the compound;
- [056] FIG. 25 is a plot of vapor pressure of various compounds, *e.g.*, diphenyl ether, hexadecane, geranyl formate and caproic acid, versus temperature;

[057] FIG. 26 is a plot of blood levels for both the IV dose and the inhalation dose administered to various dogs during the experiments using the system shown in FIG. 1;

[058] FIG. 27 is a plot of calculated and experimental mass median diameter (MMD) versus compound mass in the range of 10 to 310  $\mu\text{g}$ ;

[059] FIG. 28 is a plot of calculated and experimental MMD versus compound mass in the range of 10 to 310  $\mu\text{g}$ ; and

[060] FIG. 29 is a plot of the theoretical size (diameter) of an aerosol as a function of the ratio of the vaporized compound to the volume of the mixing gas.

## DETAILED DESCRIPTION

### *Definitions*

[061] “Aerodynamic diameter” of a given particle refers to the diameter of a spherical droplet with a density of 1 g/mL (the density of water) that has the same settling velocity as the given particle.

[062] “Aerosol” refers to a suspension of solid or liquid particles in a gas.

[063] “Amorphous particle” refers to a particle that does not contain more than 50 percent by weight of a crystalline form. Preferably, the particle does not contain more than 25 percent of a crystalline form. More preferably, the particle does not contain more than 10 percent of a crystalline form.

[064] “Decomposition index” refers to a number derived from an assay described in Example 7. The number is determined by subtracting the percent purity of the generated aerosol from 1.

[065] “Drug” refers to any chemical compound that is used in the prevention, diagnosis, treatment, or cure of disease, for the relief of pain, or to control or improve any physiological or pathological disorder in humans or animals. Such compounds are oftentimes listed in the Physician’s Desk Reference (Medical Economics Company, Inc. at Montvale, NJ, 56<sup>th</sup> edition, 2002), which is herein incorporated by reference.

[066] Exemplary drugs include the following: cannabinoid extracts from cannabis, THC, ketorolac, fentanyl, morphine, testosterone, ibuprofen, codeine, nicotine, Vitamin A, Vitamin E acetate, Vitamin E, nitroglycerin, pilocarpine, mescaline, testosterone enanthate, menthol, phencaramkde, methsuximide, eptastigmine, promethazine, procaine, retinol, lidocaine,



trimeprazine, isosorbide dinitrate, timolol, methypylon, etamiphyllin, propoxyphene, salmetrol, vitamin E succinate, methadone, oxprenolol, isoproterenol bitartrate, etaqualone, Vitamin D3, ethambutol, ritodrine, omoconazole, cocaine, lomustine, ketamine, ketoprofen, cilazaprol, propranolol, sufentanil, metaproterenol, prentoxapylline, testosterone proprionate, valproic acid, acebutolol, terbutaline, diazepam, topiramate, pentobarbital, alfentanil HCl, papaverine, nicergoline, fluconazole, zafirlukast, testosterone acetate, droperidol, atenolol, metoclopramide, enalapril, albuterol, ketotifen, isoproterenol, amiodarone HCl, zileuton, midazolam, oxycodone, cilostazol, propofol, nabilone, gabapentin, famotidine, lorezepam, naltrexone, acetaminophen, sumatriptan, bitolterol, nifedipine, Phenobarbital, phentolamine, 13-cis retinoic acid, droprenilamin HCl, amlodipine, caffeine, zopiclone, tramadol HCl, pirbuterol naloxone, meperidine HCl, trimethobenzamide, nalmefene, scopolamine, sildenafil, carbamazepine, procaterol HCl, methysergide, glutathione, olanzapine, zolpidem, levorphanol, buspirone and mixtures thereof.

**[067]** Typically, the drug of the composition is of one of the following classes: antibiotics, anticonvulsants, antidepressants, antiemetics, antihistamines, antiparkinsonian drugs, antipsychotics, anxiolytics, drugs for erectile dysfunction, drugs for migraine headaches, drugs for the treatment of alcoholism, drugs for the treatment of addiction, muscle relaxants, nonsteroidal anti-inflammatories, opioids, other analgesics, cannabinoids, and stimulants.

**[068]** Typically, where the drug is an antibiotic, it is selected from one of the following compounds: cefmetazole; cefazolin; cephalixin; cefoxitin; cephacetrile; cephaloglycin; cephaloridine; cephalosporins, such as cephalosporin C; cephalotin; cephamycins, such as cephamycin A, cephamycin B, and cephamycin C; cepharin; cephradine; ampicillin; amoxicillin; hetacillin; carfecillin; carindacillin; carbenicillin; amylpenicillin; azidocillin; benzympenicillin; clometocillin; cloxacillin; cyclacillin; methicillin; nafcillin; 2-pentenylpenicillin; penicillins, such as penicillin N, penicillin O, penicillin S, penicillin V; chlorobutin penicillin; dicloxacillin; diphenicillin; heptylpenicillin; and metampicillin.

**[069]** Typically, where the drug is an anticonvulsant, it is selected from one of the following compounds: gabapentin, tiagabine, and vigabatrin.

**[070]** Typically, where the drug is an antidepressant, it is selected from one of the following compounds: amitriptyline, amoxapine, benmoxine, butriptyline, clomipramine, desipramine, dosulepin, doxepin, imipramine, kitanserin, lofepramine, medifoxamine, mianserin,

maprotiline, mirtazapine, nortriptyline, protriptyline, trimipramine, viloxazine, citalopram, cotinine, duloxetine, fluoxetine, fluvoxamine, milnacipran, nisoxetine, paroxetine, reboxetine, sertraline, tianeptine, acetaphenazine, binedaline, brofaromine, cericlamine, clovoxamine, iproniazid, isocarboxazid, moclobemide, phenylhydrazine, phenelzine, selegiline, sibutramine, tranlycypromine, ademetionine, adrafinil, amesergide, amisulpride, amperozide, benactyzine, bupropion, caroxazone, gepirone, idazoxan, metralindole, milnacipran, minaprine, nefazodone, nomifensine, ritanserin, roxindole, S-adenosylmethionine, tofenacin, trazodone, tryptophan, venlafaxine, and zalospirone.

[071] Typically, where the drug is an antiemetic, it is selected from one of the following compounds: alizapride, azasetron, benzquinamide, bromopride, buclizine, chlorpromazine, cinnarizine, clebopride, cyclizine, diphenhydramine, diphenidol, dolasetron methanesulfonate, dronabinol, droperidol, granisetron, hyoscine, lorazepam, metoclopramide, metopimazine, ondansetron, perphenazine, promethazine, prochlorperazine, scopolamine, triethylperazine, trifluoperazine, triflupromazine, trimethobenzamide, tropisetron, domeridone, and palonosetron.

[072] Typically, where the drug is an antihistamine, it is selected from one of the following compounds: azatadine, brompheniramine, chlorpheniramine, clemastine, cyproheptadine, dexmedetomidine, diphenhydramine, doxylamine, hydroxyzine, cetirizine, fexofenadine, loratidine, and promethazine.

[073] Typically, where the drug is an antiparkinsonian drug, it is selected one of the following compounds: amantadine, baclofen, biperiden, benztropine, orphenadrine, procyclidine, trihexyphenidyl, levodopa, carbidopa, selegiline, deprenyl, andropinirole, apomorphine, benserazide, bromocriptine, budipine, cabergoline, dihydroergokryptine, eliprodil, eptastigmine, ergoline pramipexole, galanthamine, lazabemide, lisuride, mazindol, memantine, mofegiline, pergolike, pramipexole, propentofylline, rasagiline, remacemide, spheramine, terguride, entacapone, and tolcapone.

[074] Typically, where the drug is an antipsychotic, it is selected from one of the following compounds: acetophenazine, alizapride, amperozide, benperidol, benzquinamide, bromperidol, buramate, butaperazine, carphenazine, carpipramine, chlorpromazine, chlorprothixene, clocapramine, clomacran, clopenthixol, clospirazine, clothiapine, cyamemazine, droperidol, flupenthixol, fluphenazine, fluspirilene, haloperidol, mesoridazine,

metofenazate, molindrone, penfluridol, pericyazine, perphenazine, pimozide, pipamerone, piperacetazine, pipotiazine, prochlorperazine, promazine, remoxipride, sertindole, spiperone, sulpiride, thioridazine, thiothixene, trifluperidol, triflupromazine, trifluoperazine, ziprasidone, zotepine, zuclopenthixol, amisulpride, butaclamol, clozapine, melperone, olanzapine, quetiapine, and risperidone.

**[075]** Typically, where the drug is an anxiolytic, it is selected from one of the following compounds: mecloqualone, medetomidine, metomidate, adinazolam, chlordiazepoxide, clobenzepam, flurazepam, lorazepam, loprazolam, midazolam, alpidem, alseroxlon, amphenidone, azacyclonol, bromisovalum, buspirone, calcium N-carboamoylaspartate, captodiamine, capuride, carbcloral, carbromal, chloral betaine, enciprazine, flesinoxan, ipsapiraone, lesopitron, loxapine, methaqualone, methprylon, propranolol, tandospirone, trazadone, zopiclone, and zolpidem.

**[076]** Typically, where the drug is a drug for erectile dysfunction, it is selected from one of the following compounds: cialis (IC351), sildenafil, vardenafil, apomorphine, apomorphine diacetate, phentolamine, and yohimbine.

**[077]** Typically, where the drug is a drug for migraine headache, it is selected from one of the following compounds: almotriptan, alperopride, codeine, dihydroergotamine, ergotamine, eletriptan, frovatriptan, isometheptene, lidocaine, lisuride, metoclopramide, naratriptan, oxycodone, propoxyphene, rizatriptan, sumatriptan, tolfenamic acid, zolmitriptan, amitriptyline, atenolol, clonidine, cyproheptadine, diltiazem, doxepin, fluoxetine, lisinopril, methysergide, metoprolol, nadolol, nortriptyline, paroxetine, pizotifen, pizotyline, propranolol, protriptyline, sertraline, timolol, and verapamil.

**[078]** Typically, where the drug is a drug for the treatment of alcoholism, it is selected from one of the following compounds: naloxone, naltrexone, and disulfiram.

**[079]** Typically, where the drug is a drug for the treatment of addiction it is buprenorphine.

**[080]** Typically, where the drug is a muscle relaxant, it is selected from one of the following compounds: baclofen, cyclobenzaprine, orphenadrine, quinine, and tizanidine.

**[081]** Typically, where the drug is a nonsteroidal anti-inflammatory, it is selected from one of the following compounds: aceclofenac, alminoprofen, amfenac, aminopropylon, amixetrine, benoxaprofen, bromfenac, bufexamac, carprofen, choline, salicylate, cinchophen,

cinmetacin, clopiac, clometacin, diclofenac, etodolac, indoprofen, mazipredone, meclofenamate, piroxicam, pirprofen, and tolfenamate.

[082] Typically, where the drug is an opioid, it is selected from one of the following compounds: alfentanil, allylprodine, alphaprodine, anileridine, benzylmorphine, bezitramide, buprenorphine, butorphanol, carbiphen, cipramadol, clonitazene, codeine, dextromoramide, dextropropoxyphene, diamorphine, dihydrocodeine, diphenoxylate, dipipanone, fentanyl, hydromorphone, L-alpha acetyl methadol, lofentanil, levorphanol, meperidine, methadone, meptazinol, metopon, morphine, nalbuphine, nalorphine, oxycodone, papaveretum, pethidine, pentazocine, phenazocine, remifentanil, sufentanil, and tramadol.

[083] Typically, where the drug is an other analgesic it is selected from one of the following compounds: apazone, benzpiperylon, benzydramine, caffeine, clonixin, ethoheptazine, flupirtine, nefopam, orphenadrine, propacetamol, and propoxyphene.

[084] Typically, where the drug is a cannabinoid, it is tetrahydrocannabinol (*e.g.*, delta-8 or delta-9).

[085] Typically, where the drug is a stimulant, it is selected from one of the following compounds: amphetamine, brucine, caffeine, dexfenfluramine, dextroamphetamine, ephedrine, fenfluramine, mazindol, methyphenidate, pemoline, phentermine, and sibutramine.

[086] "Drug degradation product" refers to a compound resulting from a chemical modification of a drug. The modification, for example, can be the result of a thermally or photochemically induced reaction. Such reactions include, without limitation, oxidation and hydrolysis.

[087] "Mass median aerodynamic diameter" or "MMAD" of an aerosol refers to the aerodynamic diameter for which half the particulate mass of the aerosol is contributed by particles with an aerodynamic diameter larger than the MMAD and half by particles with an aerodynamic diameter smaller than the MMAD.

[088] "Stable aerosol" refers to an aerosol where the MMAD of its constituent particles does not vary by more than 50% over a set period of time. For example, an aerosol with an MMAD of 100 nm is stable over 1 s, if at a time 1 second later it has an MMAD between 50 nm and 150 nm. Preferably, the MMAD does not vary by more than 25% over a set period

of time. More preferably, the MMAD does not vary by more than 20%, 15%, 10% or 5% over time.

### ***Aerosolization Device***

[089] Example 1 is described in terms of an *in vivo* dog experiment. The example, however, is easily modified to suit human inhalation primarily through increasing airflow through it.

[090] Referring to FIGS. 1-8, a first example (1) of an aerosolization device of the present invention will be described. The device 1 as shown in FIG. 1 is operably connected to flow meter 4 (e.g., a TSI 4100 flow meter). The readings from flow meter 4 are fed to the electronics within chassis 8 shown in FIG. 2. Flow meter 4 is shown in FIG. 1 within a dotted line to indicate housing 10. Device controller 20 includes Chembook model # N30W laptop computer having actuator switch 22 (FIG. 3) and National Instruments I/O Board (model #SC2345) (not shown) that interfaces with computer 20 to control device 1 and to control the recording of all data collected during the experiments. A software program to carry out these functions was developed using National Instruments' Labview software program.

[091] Connection between device 1 and the I/O board is accomplished with a cable (e.g., DB25, not shown). A standard power supply (e.g., Condor F15-15-A+ not shown) delivers power to device 1. Inhalation controller 30 is used to control the rate and volume of inhalation through device 1 into an anesthetized dog through an endotracheal tube 34. Controller 30 has a programmable breath hold delay, at the end of which, exhaust valve 40 in exhaust line 42 opens and the dog is allowed to exhale. Filter 50 in line 42 measures the amount of exhaust and its composition to monitor any exhaled drug. The source air through inlet line 54, inlet valve 58, flow meter 4 and inlet orifice 59 is from a compressed air cylinder (not shown).

[092] Now referring to FIGS. 3-5 and 7, a dose of compound 60 is deposited onto thin, stainless steel foil 64 so that the thickness of compound 60 is less than 10 microns. In most cases, compound 60 is deposited by making a solution of the compound with an organic solvent. This mixture is then applied to the foil substrate with an automated pump system. As shown, the size of the entire foil 64 (e.g., alloy of 302 or 304 with 0.004 in. thickness) is 0.7

by 2.9 inches and the area in which compound **60** is deposited is 0.35 by 1.6 inches. Other foil materials can be used but stainless steel has an advantage over other materials like aluminum in that it has a much lower thermal conductivity value, while not appreciably increasing the thermal mass. A low thermal conductivity is helpful because the heat generated in foil **64** should stay in the area of interest (*i.e.*, the heating/vaporization zone **70**). Foil **64** should have a constant cross section, because otherwise the electrical currents induced by the heater will not be uniform. Foil **64** is held in frame **68**, made so that the trailing edge of foil **64** has no lip on movable slide **78** and so compound **60**, once mixed with the air, is free in a downstream direction as indicated by arrow 127 of FIG. 3. Frame **68** is typically made of a non-conductive material to withstand moderate heat (*e.g.*, 200°C) and to be non-chemically reactive with the compound (*e.g.*, DELRIN AF®, a copolymer of acetal and TEFLON®).

[093] Sub-assembly **80**, shown in FIG. 7, consists of frame **68** having compound (**60**) coated foil **64** mounted therein. Sub-assembly **80** is secured within movable slide **78** by setting each of the downstream, tapered ends of frame **68** to abut against small rods **86** protruding from each downstream end of slide **78**, as shown in FIG. 7. Slide **78** is driven by stepper motor **88**, shown in FIG. 3, that moves sub-assembly **80** containing compound **60** along the longitudinal axis of example 1. This, in turn, moves stainless steel foil **64** through an alternating magnetic field. (It is preferable for the magnetic field to be confined within heating/vaporization zone **70**, shown in FIG. 5, as in this laboratory example.) Ferrite toroid **90** is used to direct the magnetic field and is placed below foil **64** (*e.g.*, approximately 0.05 inches below). As shown in FIG. 5, heated area **70** is approximately 0.15 by 0.4 inches, with the smaller dimension along the direction of travel from left to right (*i.e.*, from the upstream to the downstream ends of device 1) and the large dimension across the direction of travel (*i.e.*, the width of device 1).

[094] Foil **64** functions as both a substrate for the drug to be delivered to the subject and the heating element for the vaporization of the drug. Heating element **64** is heated primarily by eddy currents induced by an alternating magnetic field. The alternating magnetic field is produced in ferrite toroid **90** (*e.g.*, from Fair-Rite Company) with slit **94** (*e.g.*, 0.10 in. wide), which was wrapped with coil **98** of copper magnet wire. When an alternating current is passed through coil **98**, an alternating magnetic field is produced in ferrite toroid **90**. A

magnetic field fills the gap formed by slit **94** and magnetic field fringe lines **100**, shown in FIGS. 5 and 6, extend out from toroid **90**. The magnetic field line fringe lines **100** intersect heating element **64**. When using a ferrite core, the alternating frequency of the field is limited to below 1 MHz. In this device, a frequency between 100 and 300 kHz is typically used.

[095] The location and geometry of the eddy currents determine where foil **64** will be heated. Since magnetic field fringe lines **100** pass through foil **64** twice, once leaving ferrite toroid **90** and once returning, two rings of current are produced, and in opposite directions. One of the rings is formed around magnetic field lines **100** that leave toroid **90** and the other ring forms around magnetic field lines **100** that return toroid **90**. The rings of current overlap directly over the center of slit **94**. Since they were in opposite directions, they sum together. The greatest heating effect is therefore produced over the center of slit **94**.

[096] Slide **78** and its contents are housed in airway **102** made up of upper airway section **104** and lower airway section **108** shown in FIG. 3. Upper airway section **104** is removable and allows the insertion of movable slide **78**, sub-assembly **80** and foil **64**. Lower airway section **108** is mounted on top of chassis **8** that houses the electronics (not shown), magnetic field generator **110**, stepper motor **88** and position sensors (not shown). Referring again to FIG. 1, mounted in upper airway section **104** is upstream passage **120** and inlet orifice **59** that couples upper airway section **104** to flow meter **4**. The readings from the flow meter **4** are fed to the electronics housed in chassis **8**. Additionally, at the downstream end of airway passage **102**, outlet **124** is connected to mouthpiece **126**. During administration of compound **60** to the dog, when joined to the system, air is forced through inlet line **54**, flow meter **4**, airway **102**, and outlet **124** into the dog.

[097] Additionally, a pyrometer at the end of TC2 line **130** is located within airway **102** and is used to measure the temperature of foil **64**. Because of the specific geometry of the example shown in FIGS. 1-7, the temperature reading of foil **64** is taken after heating zone **70**. Calibration of the thermal decay between heating zone **70** and the measurement area is required. Temperature data is collected and used for quality control and verification and not to control any heating parameters. A second temperature sensor is located at the end of TC1 line **132** in outlet **124** and is used to monitor the temperature of the air delivered to the dog.

[0098] In a preferred example of the experimental device, removable block **140**, mounted on upper airway section **104**, restricts a cross-sectional area of airway **102** and provides a specific mixing geometry therein. In this preferred example, airway **140** lowers the roof of upper airway section **104** (*e.g.*, to within 0.04 inch of) with respect to foil **64**. Additionally, block **140** contains baffles (*e.g.*, 31 steel rods 0.04 in. in diameter, not shown). The rods are oriented perpendicular to the foil and extend from the top of upper airway section **104** to within a small distance of the foil (*e.g.*, 0.004 in.). The rods are placed in a staggered pattern and have sharp, squared off ends, which cause turbulence as air passes around them. This turbulence assures complete mixing of vaporized compounds with air passing through the device.

[0099] A second example (**150**) of an aerosolization device of the present invention, in which the cross-sectional area is also restricted along the gas/vapor mixing area, will be described in reference to FIG. 9. In this example, venturi tube **152** within housing **10** having inlet **154**, outlet **156** includes a throat **158** between inlet **154** and outlet **156**, which is used to restrict the gas flow through venturi tube **152**. Additionally, a controller **160** is designed to control the flow of air passing through a valve **164** based on readings from the thermocouple **168** of the temperature of the air, which can be controlled by heater **166**.

[0100] Block **140** is located directly over heating zone **70** and creates a heating/vaporization/mixing zone. Prior to commencing aerosol generation, slide **78** is in the downstream position. Slide **78**, with its contents, is then drawn upstream into this heating/vaporization/mixing zone **70** as energy is applied to foil **64** through the inductive heater system described in detail below.

[0101] The device of the present invention is optionally equipped with an annunciating device. One of the many functions for the annunciating device is to alert the operator of the device that a compound is not being vaporized or is being improperly vaporized. The annunciating device can also be used to alert the operator that the gas flow rate is outside a desired range. FIG. 6 is a schematic diagram illustrating a third example of a hand held aerosolization device **180** of the present invention. As shown, device **180** includes many of the components of device **150**, discussed above, and additionally includes an annunciating device **170**. During the use of device **180** in which the patient's inhalation rate controls the airflow rate, a signal from annunciating device **170** would alert the patient to adjust the



inhalation rate to the desired range. In this case, controller **160** would be connected to annunciating device **170** to send the necessary signal that the flow rate was not within the desired range.

[0102] The induction drive circuit **190** shown in FIG. 8 is used to drive the induction-heating element of device **1**. The purpose of circuit **190** is to produce an alternating current in drive coil **98** wrapped around ferrite core **90**. Circuit **190** consists of two P-channel transistors **200** and two N-channel MOSFET transistors **202** arranged in a bridge configuration. MOSFET transistors **200** and **202** connected to clock pulse generator **219** are turned on and off in pairs by D-type flip-flop **208** through MOSFET transistor drive circuit **210**. D-type flip-flop **208** is wired to cause the Q output of the flip-flop to alternately change state with the rising edge of the clock generation signal. One pair of MOSFET transistors **200** is connected to the Q output on D-type flip-flop **208** and the other pair, **202**, is connected to the Q-not output of flip-flop **208**. When Q is high (5 Volts), a low impedance connection is made between the D.C. power supply (not shown) and the series combination of drive coil **98** and the capacitor through the pair of MOSFET transistors **200** controlled by the Q output. When D-type flip-flop **208** changes state and Q-not is high, the low impedance connection from the power supply to the series combination drive coil **98** and capacitor **220** is reversed. Since flip-flop **208** changes state on the rising edge of the clock generation signal, two flip-flop changes are required for one complete drive cycle of the induction-heating element. The clock generation signal is typically set at twice the resonant frequency of the series combination of drive coil **90** and capacitor **220**. The clock signal frequency can be manually or automatically set.

[0103] A second example (**150**) of an aerosolization device of the present invention, in which the cross-sectional area is also restricted along the gas/vapor mixing area, will be described in reference to FIG. 9. In this example, venturi tube **152** within housing **10** having inlet **154**, outlet **156** and throat **158** between inlet **154** and outlet **156** is used to restrict the gas flow through venturi tube **152**. Controller **160** is designed to control the flow of air passing through valve **164** based on readings from the thermocouple **168** of the temperature of the air as a result of heater **166**.

[0104] A fourth example (**300**) of an aerosolization device of the present invention will be described in reference to FIGS. 10 and 11. A gas stream is passed into thin walled tube **302** having a coating (**310**) of compound **60** on its inside. The flow rate of the gas stream is

controlled by valve **314**. The device of example **300**, as with others, allows for rapid heat-up using a resistive heating system (**320**) while controlling the flow direction of vaporized compound. After activating heating system **320** with actuator **330**, current is passed along tube **302** in the heating/vaporization zone **340** as the carrier gas (*e.g.*, air, N<sub>2</sub> and the like) is passed through tube **302** and mixes with the resulting vapor.

[0105] FIG. 12 shows an alternative heating system to resistive heating system **320** used in connection with the fourth example. In this case, inductive heating system **350** consists of a plurality of ferrites **360** for conducting the magnetic flux to vaporize compound **310**.

[0106] FIG. 13 shows a variation on the fourth example in which flow restrictor **370** is mounted within thin-walled tube **302** by means of support **374** within a housing (not shown) to increase the flow of mixing gas across the surface of compound **310**.

[0107] A fifth example **400** of an aerosolization device of the present invention will be described in reference to FIG. 14. For this example, compound **60** is placed within expandable container **402** (*e.g.*, a foil pouch) and is heated by resistance heater **406**, which is activated by actuator **410** as shown in FIG. 14. The vaporized compound generated is forced into container **420** through outlet passage **440** and mixed with the gas flowing through tube **404**. Additional steps are taken, when necessary, to preclude or retard decomposition of compound **60**. One such step is the removal or reduction of oxygen around **60** during the heat up period. This can be accomplished, for example, by sealing the small container housing in an inert atmosphere.

[0108] A sixth example **500** of an aerosolization device of the present invention will be described in reference to FIG. 15. Compound **60** is placed in an inert atmosphere or under a vacuum in container **502** within housing **10** and is heated by resistance heater **504** upon being activated by actuator **508** as shown in FIG. 15. Once compound **60** has become vaporized it can then be ejected through outlet passage **510** into the air stream passing through tube **520**.

[0109] FIG. 16 shows a variation of device **500** in which fan **530** recirculates the inert atmosphere over the surface of compound **60**. The inert gas from a compressed gas cylinder (not shown) enters through inlet **540** and one-way valve **550** and exits through outlet passage **510** into tube **502**.

[0110] A seventh example (**600**) of an aerosolization device of the present invention will be described in reference to FIG. 17. A compound (not shown), such as compound **60** discussed

above, is deposited onto a substrate in the form of discrete particles **602** (e.g., aluminum oxide (alumina), silica, coated silica, carbon, graphite, diatomaceous earth, and other packing materials commonly used in gas chromatography). The coated particles are placed within first tube **604**, sandwiched between filters **606** and **608**, and heated by resistance heater **610**, which is activated by actuator **620**. The resulting vapor from tube **604** is combined with the air or other gas passing through second tube **625**.

[0111] FIG. 18 shows a variation of device **600** in which resistance heater **630** heats the air prior to passing through first tube **604** and over discrete particles **602**.

[0112] An eighth example **700** of an aerosolization device of the present invention will be described in reference to FIG. 19. Compound **60** is deposited into chamber **710** and is heated by resistance heater **715**, which is activated by actuator **720**. Upon heating, some of compound **60** is vaporized and ejected from chamber **710** by passing an inert gas entering housing **10** through inert gas inlet **725** and valve **728** across the surface of the compound. The mixture of inert gas and vaporized compound passes through passage **730** and is then mixed with a gas passing through tube **735**.

[0113] A ninth example **800** of an aerosolization device of the present invention will be described in reference to FIG. 20. Thermally conductive substrate **802** is heated by resistance heater **810** at the upstream end of tube **820**, and the thermal energy is allowed to travel along substrate **802**. This produces, when observed in a particular location, a heat up rate that is determined from the characteristics of the thermally conductive substrate. By varying the material and its cross sectional area, it was possible to control the rate of heat up. The resistive heater is embedded in substrate **802** at one end. However, it could be embedded into both ends, or in a variety of positions along the substrate and still allow the temperature gradient to move along the carrier and/or substrate.

[0114] A tenth example **900** of an aerosolization device of the present invention will be described in reference to FIGS. 21 and 22. Air is channeled through a fine mesh metal screen **902** on which drug is deposited. Screen **902** is positioned across airway passage **910** (e.g., constructed from 18 mm glass tubing). The two sides of the screen are electrically connected to charged capacitor **920** through silicon-controlled rectifier (SCR) **922** to make a circuit. The charge of the capacitor is calculated and set at a value such that, when actuator

930 closes SCR 922, the energy from capacitor 920 is converted to a desired temperature rise in screen 902.

### ***General Considerations***

[0115] The device of the present invention utilizes a flow of gas (*e.g.*, air) across the surface of a compound (60) to sweep away vaporized molecules. This process drives vaporization as opposed to condensation and therefore enables aerosol formation at relatively moderate temperatures. Nicotine (1 mg, bp 247 °C/745 mm), for example, vaporized in less than 2 s at about 130 °C in a device of the present invention. Similarly, fentanyl (bp >300 °C/760 mm) was vaporized around 190 °C in quantities up to 2 mg.

[0116] Purity of an aerosol produced using a device of the present invention is enhanced by limiting the time during which a compound (60) is exposed to elevated temperatures. This is accomplished by rapidly heating a thin film of the compound to vaporize it. The vapors are then immediately cooled upon entry into a carrier gas stream.

[0117] Typically, compound 60 is subjected to a temperature rise of at least 1,000 °C/second. In certain cases, the compound is subjected to a temperature rise of at least 2,000 °C/second, 5,000 °C/second, 7,500 °C or 10,000 °C/second. A rapid temperature rise within the compound is facilitated when it is coated as a thin film (*e.g.*, between 10 μ and 10 nm in thickness). The compound is oftentimes coated as a film between 5 μ and 10 nm, 4 μ and 10 nm, 3 μ and 10 nm, 2 μ and 10 nm, or even 1 μ to 10 nm in thickness.

[0118] Rapid temperature rises and thin coatings ensure that compounds are substantially vaporized in a short time. Typically, greater than 0.1 mg, 0.25 mg, 0.5 mg, 0.75 mg or 1 mg of a compound is vaporized in less than 100 milliseconds from the start of heating.

Oftentimes, the same amount of compound is vaporized in less than 75 milliseconds, 50 milliseconds, 25 milliseconds, or 10 milliseconds from the start of heating.

[0119] Examples of compounds that have benefited from rapid heating in a device of the present invention include lipophilic substance #87 and fentanyl. Lipophilic substance #87 decomposed by more than 90% when heated at 425 °C for 5 minutes, but only 20 % when the temperature was lowered to 350 °C. Decomposition of the substance was further lowered to about 12% when the heating time was decreased to 30 seconds and to less than 2% at 10-50 milliseconds. A fentanyl sample decomposed entirely when heated to 200 °C for 30 seconds,

and only 15-30% decomposed when heated for 10 milliseconds. Vaporizing fentanyl in device 1 led to less than 0.1% decomposition.

[0120] An aerosol of the present invention contains particles having an MMAD between 10 nm and 1  $\mu$ , preferably 10 nm to 900 nm, 10 nm to 800 nm, 10 nm to 700 nm, 10 nm to 600 nm, 10 nm to 500 nm, 10 nm to 400 nm, 10 nm to 300 nm, 10 nm to 200 nm, or 10 nm to 100 nm. Particles are produced such that their size is stable for several seconds (*e.g.*, 1 to 3 s). The aerosol particle size and subsequent stability is controlled by the rate of compound vaporization, the rate of carrier gas introduction, and the mixing of resultant vapors and the carrier gas. Such control is accomplished using a number of methods, including the following: (a) measuring the quantity and regulating the flow rate of the mixing air; and/or, (b) regulating the vaporization rate of the compound (*e.g.*, by changing the energy transferred to the compound during the heating process or changing the amount of compound introduced into a heating region).

[0121] A desired particle size is achieved by mixing a compound in its vapor state into a volume of a carrier gas in a ratio such that, when the number concentration of the mixture reaches approximately  $10^9$  particles/mL, a particle that exists in a size range from 10 nm to 1  $\mu$  for 1 to 3 seconds results.

[0122] FIG. 23 is a plot of theoretical data calculated from a mathematical model. *See* "Aerosol Technology" W. C. Hinds, second edition 1999, Wiley, New York. It shows the time in seconds it takes for the number concentration of an aerosol to aggregate to half of its original value as a function of the particle concentration. For example, a 1.0 mg vaporized dose of a compound with a molecular weight of 200 that is mixed into 1 liter of air will have approximately  $3 \times 10^{18}$  molecules (particles) in the liter. This results in a number concentration of  $3 \times 10^{15}$ /cc. Extrapolating from FIG. 23, one can see that it takes less than 10 milliseconds for the number of particles to halve in this example. Therefore, to insure uniform mixing of a vaporized compound, the mixing must occur in a very short time. FIG. 23 also shows that when the number concentration of the mixture reaches approximately  $10^9$  particles/cc, the particle size is "stable" for the purpose of drug delivery by inhalation.

[0123] FIG. 23 is for an aerosol having a Coagulation Coefficient (K) of  $5 \times 10^{-16}$  meters<sup>3</sup>/second. This K value corresponds to a particle size of 200 nm. As the particle size changes, so can its K value. Table 1 below gives the K values for various particle sizes. As

K increases, the time required for the aerosol to aggregate from a particular particle size to a larger particle size is reduced. As can be seen from Table 1 and FIG. 24, when the particle is in the 10 nm to 100 nm range, the effect of a changing K value tends to accelerate the coagulation process towards 100 nm in size.

**Table 1**

Particle size (diameter in nm)	Coagulation Coefficient ( $\times e^{-15}$ meters <sup>3</sup> /second)
1	3.11
5	6.93
10	9.48
20	11.50
50	9.92
100	7.17
200	5.09
500	3.76
1000	3.35
2000	3.15
5000	3.04
10000	3.00

[0124] In creating an aerosol of a particular particle size, the ratio of mass of vaporized compound to the volume of the mixing gas is the controlling condition. By changing this ratio, the particle size can be manipulated (see FIG. 29). However, not all compounds and not all gases, with the same ratio will result in the same particle size distribution (PSD). Other factors must be known to be able to accurately predict the resultant particle size. A compound's density, polarity, and temperature are examples of some of these factors. Additionally, whether the compound is hydrophilic or hydrophobic will affect the eventual particle size, because this factor affects an aerosol's tendency to grow by taking on water from the surrounding environment.

[0125] In order to simplify the approach used to predict the resulting particle size, the following assumptions were made:

1. The compound is non polar (or has a weak polarity).
2. The compound is hydrophobic or hydrophilic with a mixing gas that is dry.
3. The resultant aerosol is at or close to standard temperature and pressure.
4. The coagulation coefficient is constant over the particle size range and therefore the number concentration that predicts the stability of the particle size is constant.

[0126] Consequently, the following variables are taken into consideration in predicting the resulting particle size:

1. The amount (in grams) of compound vaporized.
2. The volume of gas (in cc's) that the vaporized compound is mixed into.
3. The "stable" number concentration in number of particles/cc.
4. The geometric standard deviation (GSD) of the aerosol.

[0127] Where the GSD is 1, all of the particle sizes are the same size and therefore the calculation of particle size becomes a matter of dividing a compound's mass into the number of particles given by the number concentration and from there calculating the particle size diameter using the density of the compound. The problem becomes different, though, if the GSD is other than 1. As an aerosol changes from a GSD of 1 to a GSD of 1.35, the mass median diameter (MMD) will increase. MMD is the point of equilibrium where an equal mass of material exists in smaller diameter particles as exists in larger diameter particles. Since total mass is not changing as the GSD changes, and since there are large and small particles, the MMD must become larger as the GSD increases because the mass of a particle goes up as the cube of its diameter. Therefore larger particles, in effect, carry more weight and the MMD becomes larger to "balance" out the masses.

[0128] To determine the effect of a changing GSD, one can start with the formula for the mass per unit volume of an aerosol given a known MMD, GSD, density, and number concentration. The formula is from Finlay's *"The Mechanics of Inhaled Pharmaceutical Aerosols"* (2001, Academic press). Formula 2.39 states that the mass per unit volume of an aerosol is:

$$M=(\rho N\pi/6) (MMD)^3 \exp[-9/2(\ln\sigma_g)^2]$$

Where:  $\rho$ =density in gm/cc

N=Number concentration in particles/cc

MMD = mass median diameter (in cm)

$\sigma_g$  = the GSD

M = the mass per unit volume of the aerosol in gms/cc

[0129] If the change in the MMD is considered as an aerosol changes from one GSD to another, while the density, number concentration, and the mass remain unchanged the following equality can be set up:

$$\rho N \pi / 6 (MMD_1)^3 \exp[-9/2(\ln \sigma_{g1})^2] = \rho N \pi / 6 (MMD_2)^3 \exp[-9/2(\ln \sigma_{g2})^2]$$

simplifying:

$$(MMD_1)^3 \exp[-9/2(\ln \sigma_{g1})^2] = (MMD_2)^3 \exp[-9/2(\ln \sigma_{g2})^2]$$

Or

$$(MMD_1)^3 / (MMD_2)^3 = \exp[-9/2(\ln \sigma_{g2})^2] / \exp[-9/2(\ln \sigma_{g1})^2]$$

[0130] If one sets the GSD of case 1 to 1.0 then:

$$\exp[-9/2(\ln \sigma_{g1})^2] = 1$$

And therefore:

$$(MMD_1 / MMD_2)^3 = \exp[-9/2(\ln \sigma_{g2})^2]$$

Or:

$$MMD_1 / MMD_2 = \exp[-3/2(\ln \sigma_{g2})^2]$$

[0131] It is advantageous to calculate the change in the MMD as the GSD changes. Solving for MMD<sub>2</sub> as a function of MMD<sub>1</sub> and the new GSD<sub>2</sub> yields:

$$MMD_2 = MMD_1 / \exp[-3/2(\ln \sigma_{g2})^2] \quad \text{for a } \sigma_{g1} = 1$$

[0132] To calculate MMD<sub>1</sub>, divide the compound's mass into the number of particles and then, calculate its diameter using the density of the compound.

$$MMD_1 = (6C / \rho N V \pi)^{1/3} \text{ for an aerosol with a GSD of 1}$$

Where: C = the mass of the compound in gm's

$\rho$  = Density in gm/cc (as before)

N = Number concentration in particles /cc (as before)

V = volume of the mixing gas in cc

[0133] Insertion of MMD<sub>1</sub> into the above equation leads to:

$$MMD_2 = (6C / \rho N V \pi)^{1/3} / [\exp[-3/2(\ln \sigma_{g2})^2]], \text{ measured in centimeters.}$$



[0134] A resultant MMD can be calculated from the number concentration, the mass of the compound, the compound density, the volume of the mixing gas, and the GSD of the aerosol.

[0135] The required vaporization rate depends on the particle size one wishes to create. If the particle size is in the 10 nm to 100 nm range, then the compound, once vaporized, must be mixed, in most cases, into the largest possible volume of air. This volume of air is determined from lung physiology and can be assumed to have a reasonable upper limit of 2 liters. If the volume of air is limited to below 2 liters (*e.g.*, 500cc), too large a particle will result unless the dose is exceedingly small (*e.g.*, less than 50  $\mu\text{g}$ ).

[0136] In the 10 nm to 100 nm range, doses of 1-2 mg are possible. If this dose is mixed into 2 liters of air, which will be inhaled in 1-2 seconds, the required, desired vaporization rate is in the range of about 0.5 to about 2 mg/second.

[0137] The first example of the present invention is shown in FIG. 1 and is the basic device through which the principles cited above have been demonstrated in the laboratory. This device is described in detail in the EXAMPLES.

[0138] In the second example of the present invention shown in FIG. 9, the use of a reduced airway cross section increases the speed of the air across the compound's surface to about 10 meters/second. If complete mixing is to happen within 1 millisecond, then the distance the gas and vaporized mixture must travel to achieve complete mixing must be no longer than 10 millimeters. However, it is more desirable for complete mixing to happen before the compound has aggregated to a larger size, so a desirable mixing distance is typically about 1 millimeter or less.

[0139] In the fourth example of the present invention shown in FIGS. 10-13, an aerosol having particles with an MMAD in the 10 nm to 100 nm range is generated by allowing air to sweep over a thin film of the compound during the heating process. This allows the compound to become vaporized at a lower temperature due to the lowering of the partial pressure of the compound near the surface of the film.

[0140] The fifth example shown in FIG. 14, the sixth example shown in FIGS. 15 and 16, and the eighth example shown in FIG. 19 overcome a problem with certain compounds that react rapidly with oxygen at elevated temperatures. To solve this problem, the compound is heated in an expandable container (fourth example), a small container housing under a vacuum or containing a small amount, *e.g.*, about 1 to about 10 ml, of an inert gas (fifth

example). Once a compound is vaporized and mixed with an inert gas while the gaseous mixture is maintained at a temperature sufficient to keep the compound in its vaporized state, the gaseous mixture is then injected into an air stream. The volume of inert gas can also be re-circulated over the surface of the heated compound to aid in its vaporization as shown in FIG. 16. In the seventh example, the compound is introduced into the gas as a pure vapor. This involves vaporizing the compound in an oven or other container and then injecting the vapor into an air or other gas stream through one or more mixing nozzles.

**[0141]** In the sixth example shown in FIGS. 17-18, gas is passed through a first tube and over discrete substrate particles, having a large surface area to mass ratio, and coated with the compound. The particles are heated as shown in FIG. 17 to vaporize the compound, or the gas is heated and the heated gas vaporizes the compound as shown in FIG. 18. The gaseous mixture from the first tube is combined with the gas passing through second tube to rapidly cool the mixture before administering it to a patient.

**[0142]** The eighth example shown in FIG. 20 is a thermal gradient device that is similar to device 1 used in the laboratory experiments. This example also has a moving heating zone without any moving parts, accomplished by establishing a heat gradient that transverses from one end of the device to the other over time. As the heating zone moves, exposed portions of the compound are sequentially heated and vaporized. In this manner the vaporized compound can be introduced into a gas stream over time.

**[0143]** The ninth example shown in FIGS. 21-22 is the screen device and is preferred for generating a aerosols containing particles with an MMAD greater than 100 nm. In this example, air is channeled through a fine mesh screen upon which the drug to be administered to the patient has been deposited.

**[0144]** The examples above can create aerosols without significant drug decomposition. This is accomplished while maintaining a required vaporization rate for particle size control by employing a short duration heating cycle. An airflow over the surface of the compound is established such that when the compound is heated and reaches the temperature where vaporization is first possible, the resulting compound vapors will immediately cool in the air. In the preferred examples, this is accomplished by extending the increased velocity and mixing region over an area that is larger than the heating zone region. As a result, precise control of temperature is not necessary since the compound vaporizes the instant its

vaporization temperature is reached. Additionally because mixing is also present at the point of vaporization, cooling is accomplished quickly upon vaporization.

[0145] Application of the present invention to human inhalation drug delivery must accommodate constraints of the human body and breathing physiology. Many studies of particle deposition in the lung have been conducted in the fields of public health, environmental toxicology and radiation safety. Most of the models and the *in vivo* data collected from those studies, relate to the exposure of people to aerosols homogeneously distributed in the air that they breathe, where the subject does nothing actively to minimize or maximize particle deposition in the lung. The International Commission On Radiological Protection (ICRP) models are examples of this. (See James AC, Stahlhofen W, Rudolph G, Egan MJ, Nixon W, Gehr P, Briant JK, The respiratory tract deposition model proposed by the ICRP Task Group, *Radiation Protection Dosimetry*, 1991; vol. 38: pgs.157-168).

[0146] However, in the field of aerosol drug delivery, a patient is directed to breathe in a way that maximizes deposition of the drug in the lung. This kind of breathing usually involves a full exhalation, followed by a deep inhalation sometimes at a prescribed inhalation flow rate range, e.g., about 10 to about 150 liters/minute, followed by a breath hold of several seconds. In addition, ideally, the aerosol is not uniformly distributed in the air being inhaled, but is loaded into the early part of the breath as a bolus of aerosol, followed by a volume of clean air so that the aerosol is drawn into the alveoli and flushed out of the conductive airways, bronchi and trachea by the volume of clean air that follows. A typical deep adult human breath has a volume of about 2 to 5 liters. In order to ensure consistent delivery in the whole population of adult patients, delivery of the drug bolus should be completed in the first 1-1½ liters or so of inhaled air.

[0147] As a result of the constraints of human inhalation drug delivery, a compound should be vaporized in a minimum amount of time, preferably no greater than 1 to 2 seconds. As discussed earlier, it is also advantageous, to keep the temperature of vaporization at a minimum. In order for a compound to be vaporized in 2 seconds or less and for the temperature to be kept at a minimum, rapid air movement, in the range of about 10 to about 120 liters/minute, should flow across the surface of the compound.

[0148] The following parameters are optimal in using a device of the present invention, due to human lung physiology, the physics of particle growth, and the physical chemistry of the desirable compounds:

- [0149] (1) The compound should to be vaporized over approximately 1 to 2 seconds for creation of particles in the ultra fine range.
  - [0150] (2) The compound should to be raised to the vaporization temperature as rapidly as possible.
  - [0151] (3) The compound, once vaporized, should be cooled as quickly as possible.
  - [0152] (4) The compound should be raised to the maximum temperature for a minimum duration of time to minimize decomposition.
  - [0153] (5) The air or other gas should be moved rapidly across the surface of the compound to achieve the maximum rate of vaporization.
  - [0154] (6) The heating of the air or other gas should be kept to a minimum, i.e., an increase of temperature of no greater than about 15°C above ambient.
  - [0155] (7) The compound should be mixed into the air or other gas at a consistent rate to have a consistent and repeatable particle size.
  - [0156] (8) As the gas speed increases across the compound being vaporized, the cross sectional area through the device should decrease. Furthermore, as the surface area of the compound increases the heating of the gas increases.
- [0157] The parameters of the design for one of the examples shown in FIGS. 2-5, 7 and 8 are the result of meeting and balancing the competing requirements listed above. One especially important requirement for an aerosol containing particles with an MMAD between 10 nm and 100 nm is that a compound, while needing to be vaporized within at least a 1-second period, also needs to have each portion of the compound exposed to a heat-up period that is as brief as possible. In this example, the compound is deposited onto a foil substrate and an alternating magnetic field is swept along a foil substrate heating the substrate such that the compound is vaporized sequentially over no more than about a one second period of time. Because of the sweeping action of the magnetic field, each segment of the compound has a heat-up time that is much less than one second.
- [0158] In the example noted directly above, the compound is laid down on a thin metallic foil. In one of the examples set forth below, stainless steel (alloy of 302, 304, or 316) was

used in which the surface was treated to produce a rough texture. Other foil materials can be used, but it is important that the surface and texture of the material is such that it is “wetted” by the compound when the compound is in its liquid phase, otherwise it is possible for the liquid compound to “ball” up which would defeat the design of the device and significantly change the volatilizing parameters. If the liquid compound “balls” up, the compound can be blown into and picked up by the airflow without ever vaporizing. This leads to delivery of a particle size that is uncontrolled and undesirable.

[0159] Stainless steel has advantages over materials like aluminum because it has a lower thermal conductivity value, without an appreciable increase in thermal mass. Low thermal conductivity is helpful because heat generated by the process needs to remain in the immediate area of interest.

## EXAMPLES

[0160] The following examples further illustrate the method and various examples of the present invention. These examples are for illustrative purposes and are not meant to limit the scope of the claims in any way.

### EXAMPLE 1

#### *In Vivo Results Using Example 1*

[0161] In this example, example 1, was designed to deliver an experimental dose of fentanyl between 20 µg and 500 µg, in a range of ultra fine particle sizes, in about 800 cc of air to a 10 kg dog. The lung volume of each dog under experimentation was approximately 600-700 cc and the device was designed to deliver the compound to the lung in the first half of the inhalation. Because of the value of these parameters, device 1 in this experiment can be considered a ¼ scale device for administering a dose to a human. It is believed that scaling the device to work for human subjects involves mainly increasing the airflow through the device. The time frame of the introduction of the compound into the heating/vaporization/mixing zone was set such that the compound vaporized into a volume of air that was suitable for both the volume required by dog lung anatomy (600-700cc) and the volume needed to control the ratio of the compound to the air.

[0162] The following was the sequence of events that took place during each operation:

[0163] 1. At the beginning of the run, the operator triggered inhalation controller 30 to start monitoring data from pressure transducer 240 and input flow meter 4.

[0164] 2. Controller 30 signaled controller 20 to start example 1 and to begin collecting data from the two temperature sensors and flow meter 4.

[0165] 3. After a pre-programmed delay, example 1 initiated the generation of the aerosol. (Note: there was a delay of about 0.4 seconds between the start of the controller 30 and the start of aerosol generation.)

[0166] 4. After an independent preprogrammed delay (from original trigger signal), controller 30 opened input valve 58 to start forced inhalation to a dog under experimentation.

[0167] 5. Example 1 completed the aerosol generation during the inhalation.

[0168] 6. Controller 30 monitored flow meter 4 and pressure transducer 240 throughout the inhalation and closed off flow at input valve 58 when a pre-specified volume or pressure was met. (Note: the pre-specified pressure is a safety feature to prevent injury to the subject animal. Termination of the breath at the pre-specified volume is the desirable occurrence of the experiment.)

[0169] 7. After a breath hold delay (5 seconds), exhaust valve 40 was opened and the dog was allowed to exhale.

[0170] 8. Exhaled aerosol was trapped on exhaust filter 40 for later analysis. Controller 30 recorded values for the following: volume dispensed, terminal pressure, duration of air pulse, and average flow rate. Controller 20 continuously recorded at millisecond resolution, input flow rate, exhaust flow rate, foil temperature, mouthpiece temperature, slide position, heater on/off time, and other internal diagnostic electrical parameters.

[0171] Three weight-matched female beagle dogs received fentanyl at a 100 µg intravenous bolus dose. The same dogs received fentanyl UF for Inhalation (100 µg aerosolized and administered as two successive activations of device 1, containing approximately 50µg fentanyl base) at a particle size of 80 nm (MMAD). The aerosol was administered to anesthetized dogs via the system schematically represented in FIG. 1, with a target delivered volume of 600-700 ml air, followed by a 5 second breath hold. After dosing, plasma samples for pharmacokinetic analysis were obtained at various time points from 2 min to 24 hr.

Fentanyl remaining in device 1 was recovered and measured. Fentanyl concentrations were measured by using a validated GC method, with a limit of detection of 0.2 ng/ml.

[0172] Plasma pharmacokinetics from this example were compared to intravenous (IV) fentanyl (100 µg) in the same dogs. Inhalation of fentanyl resulted in rapid absorption ( $C_{\max}$ , maximum concentration in plasma, 11.6 ng/ml and  $T_{\max}$ , maximum time, 2 min.) and high bioavailability (84%). The time course of inhaled fentanyl was nearly identical to that of IV fentanyl. Thus, fentanyl UF for inhalation had an exposure profile that was similar to that of an IV injection.

[0173] Standard non-compartmental pharmacokinetic methods were used to calculate pharmacokinetic parameters for each animal. The maximum concentration in plasma ( $C_{\max}$ ) and the maximum time it occurred ( $T_{\max}$ ) were determined by examination of the data. The area under the plasma concentration vs. time curve (AUC) was determined. The bioavailability (F) of inhaled fentanyl was determined as:

$$F = (D_{\text{IV}}/D_{\text{INHAL}}) * (AUC_{\text{INHAL}}/AUC_{\text{IV}})$$

where D was the dose and AUC was the AUC determined to the last measurable time point.

[0174] FIG. 26 plots the data obtained on the blood levels, by dog, for both the IV doses and the inhalation doses using device 1 as described above under Example 1.

[0175] The fentanyl aerosol was rapidly absorbed, with the same  $T_{\max}$  (2 min, the earliest time point) observed for both routes of administration. The maximum plasma concentration of fentanyl aerosol ( $11.6 \pm 1.9$  ng/ml) was nearly two-thirds that of IV fentanyl ( $17.6 \pm 3.6$  ng/ml). Plasma concentrations fell below the assay limit of quantitation by 6-8 hr after IV administration and by 3-4 hr after aerosol inhalation. Bioavailability calculations were based on the AUC's observed to the last measurable time point for the inhalation administration. Bioavailability for the inhalation study was 84% based on the nominal (uncorrected) fentanyl dose.

[0176] The mean plasma elimination half-life was similar after IV (75.4 min) and inhalation dose. Distribution phase half-lives (3-4 min) were also similar after both routes of administration. The inter-animal variability of pharmacokinetic parameters after the inhalation dose was low, with relative standard deviations (RSD < 25%) lower than those observed for IV administration.

## EXAMPLE 2

### *In Vitro Results Using Example 1*

[0177] Table 2 below summarizes the data collected from use of example 1 for *in vitro* testing of fentanyl. Particle size was measured with a Moudi cascade impactor.

**Table 2**

Compound Mass (ug)	Mixing air volume (cc)	MMAD (nm)	GSD
20	400	71	1.9
25	400	72-78	1.7-1.8
50	400	77-88	1.7-1.85
100	400	100-105	1.4-1.8
200	400	103-123	1.6-1.9
300	400	140-160	1.8-2.1

## EXAMPLE 3

### *Use of Example 1 to Make Fine Aerosol Particles*

[0178] In this example, example 1 was slightly modified and the flow rate changed, as discussed below, to make a fine aerosol in the 1 to 3 micron particle size range.

[0179] Airway section 140 was removed and the air channel heating/vaporization zone 70 was changed. An airway insert (not shown) had a “roof” that was 0.25 inches above the foil. There were no mixing rods as rapid mixing was not desirable in this example. Because of these two device changes, there was much less mixing with the air, thus the vapor/aerosol cloud was mixed with less air and produced a larger particle size aerosol. The airflow rate was reduced 1 liter/minute in this example. Again, this allowed the vapor to be mixed with much less air, resulting in the larger particle size aerosol.

[0180] Some operational problems with high compound loading on foil 64 in example 1 were encountered. The compound tested, dioctyl phthalate (DOP), was an oil and during the aerosolization process, a substantial quantity was blown downwind and not aerosolized. Three additional design alternatives were made to address this issue, involving changes to the substrate surface that the compound was deposited on. In the three alternatives, the substrate



was made to “hold” the compound through the use of texture. They were: a) texturing the foil; b) adding a stainless steel screen on top of the foil; and, c) replacing the foil with a fine stainless steel screen.

[0181] The results from this example are set forth below in Table 3 below:

**Table 3**

Substrate Type	MMAD, microns	GSD	Emitted Dose, ug
Textured foil	1.49 microns	1.9	97
Textured foil	2.70 microns	1.95	824
Fine screen alone	1.59 microns	1.8	441
Fine screen alone	1.66 microns	1.8	530
Screen on Foil	2.42 microns	2.2	482

[0182] As shown above, a fine particle size can be made with device 1 merely by changing the ratio of the compound to the mixing air.

#### **EXAMPLE 4**

##### *In Vitro Results Using Example 700*

[0183] A tank was partially filled with DOP and placed inside an oven (not shown) having an inlet and an outlet. DOP was used as the test compound. The tank was purged with helium prior to heating the tank and its contents to a temperature of 350°C. Helium was pumped through the tank and used to carry the DOP vapor out of the outlet. The gaseous mixture of helium and vaporized compound 60 was introduced into different size mixing tubes through a nozzle. Each of the tubes had air moving through them at 14 liters/minute. The nozzle was perpendicular to the flow direction. After this gaseous mixture was mixed with the air, the resulting aerosol was introduced into a parallel flow diffusion battery for particle size analysis. Results are set forth in Table 4 below.

**Table 4**

Mixing tube size (ID)	MMAD	GSD
4.8 mm	65 nm	1.3
14 mm	516 nm	3.3

[0184] As can be seen above, as the tube diameter became larger so did the particle size. Additionally, as the diameter became larger, the GSD also became larger. As the tube becomes larger, it is believed that the vaporized gas is introduced into a smaller segment of the mixing gas because the gas is being introduced as a point source leading to uneven mixing, which results in a large GSD.

#### **EXAMPLE 5**

##### *In Vitro Results Using Example 800*

[0185] To demonstrate effectiveness of example 800, a 4-inch long piece of aluminum was fitted with a 150-watt cartridge heater at one end. The heater was powered with a variac AC power transformer. The thickness of the aluminum was designed to ensure that heat would transverse from one end of the aluminum to the other in approximately 30 seconds.

[0186] On the topside of the aluminum, an indentation was machined to hold the compound and to hold one of two top covers. The indentation for the compound was approximately 3.5 inches long and 0.4 inches wide. The indentation was 0.025 inches deep, and was filled with 1 mg of DOP.

[0187] The first top consisted of a sheet of flat glass placed 0.04 inches above the heated surface, creating an airway. At the exit end an outlet was fitted allowing the air to be drawn into an analytical measurement device. Air was made to flow through the airway at a rate of 15 liters/minute.

[0188] In the second configuration, the top was replaced with a half cylinder made of glass. This increased the cross sectional area of the airway by an order of magnitude.

[0189] Particle size was measured with both configurations and shown to be affected by the cross sectional area of the airway.

[0190] Results from the thermal gradient test are set forth in Table 5 below:

**Table 5**

Cover size and cross- section	MMAD	GSD
Small	92 nm	1.4
Big	650 nm	unknown

[0191] As shown above, the results confirm that as the cross section becomes larger, so does the particle size.

## **EXAMPLE 6**

### *In Vitro Results Using Example 900*

[0192] In this example for producing aerosols, airway passage 910 was constructed from 18 mm diameter glass tubing. However, the passage can be made in any shape with a comparable cross-sectional area and out of any suitable material. The screen size, mesh, and the amount of compound were chosen in this example so that a gas could pass through the screen without interference once the compound had been deposited on it.

[0193] Because the internal resistance of the screen was low, i.e., between 0.01 and 0.2 ohms, the discharge rate (the RC time constant) of the capacitor was rapid, and on the order of a few milliseconds, i.e. less than 20 milliseconds, preferably in the range of about 2 to about 10 milliseconds. Upon discharge of capacitor 902 and the subsequent heating of screen 902, the deposited compound was rapidly vaporized. Because air moved through screen 902, the vaporized compound rapidly mixed with air and cooled.

[0194] The compound was deposited onto the fine stainless steel screen, e.g., 200 mesh, made from 316 stainless steel, having measurements of 2.54 cm. x 2.54 cm. The current from the capacitor was passed between one edge and another. It was not necessary to heat the screen to temperatures comparable to the thin foil in Example 1, because the compound

vaporized at a lower temperature due to the rapid air movement. Rapid air movement allowed the compound to vaporize at a lower vapor pressure, since airflow constantly removed compound vapors from the surface as soon as they were formed. Thus, the compound vaporized at a lower temperature without decomposition.

[0195] Deposition of the compound onto the screen was accomplished by mixing the compound with an organic solvent until the compound dissolved. The resulting solution was then applied to the fine stainless steel screen **902** and the solvent was allowed to evaporate. The screen was then inserted into holder **940** that electrically connected two sides of screen **902** to the power circuit described above.

[0196] A 10,000 mF capacitor was discharged while the gas was passing through screen **902**. The rapid heat up of the screen resulted in a rapid vaporization of the compound into the gas. Thus the resulting vaporized compound was mixed into a small volume of the gas. Because the ratio of the mass of the compound to the volume of the mixing gas was large, a fine (1-3 micron diameter) particle aerosol was made.

#### EXAMPLE 7

##### *General Procedure for Screening Drugs to Determine Aerosolization Preferability*

[0197] Drug (1 mg) is dissolved or suspended in a minimal amount of solvent (*e.g.*, dichloromethane or methanol). The solution or suspension is pipeted onto the middle portion of a 3 cm by 3 cm piece of aluminum foil. The coated foil is wrapped around the end of a 1½ cm diameter vial and secured with parafilm. A hot plate is preheated to approximately 300 °C, and the vial is placed on it foil side down. The vial is left on the hotplate for 10 s after volatilization or decomposition has begun. After removal from the hotplate, the vial is allowed to cool to room temperature. The foil is removed, and the vial is extracted with dichloromethane followed by saturated aqueous NaHCO<sub>3</sub>. The organic and aqueous extracts are shaken together, separated, and the organic extract is dried over Na<sub>2</sub>SO<sub>4</sub>. An aliquot of the organic solution is removed and injected into a reverse-phase HPLC with detection by absorption of 225 nm light. A drug is preferred for aerosolization where the purity of the drug isolated by this method is greater than 85%. Such a drug has a decomposition index less than 0.15. The decomposition index is arrived at by subtracting the percent purity (*i.e.*, 0.85) from 1.

**[0198]** One of ordinary skill in the art can combine the foregoing embodiments or make various other embodiments and aspects of the method and device of the present invention to adapt them to specific usages and conditions. As such, these changes and modifications are properly, equitably, and intended to be, within the full range of equivalents of the following claims.